



BORNIT® - Edge Modul

for the new basic unit BORNIT®-Flexomat 3.0



Modified bitumen emulsion with special additives for secure sealing of the elevated edge as well as for seam treatment in the base, binder and surface layers for road surface pavement made of asphalt.

Your advantages are:

- directly and cold-workable
- fast application (up to 600 m/h) with BORNIT® Flexomat 3.0 + Edge Modul
- secure sealing of the pores in the edge area
- enriched with binding agent for joint treatment in base, binder and surface layers
- handy equipment for flexible operation at small as well as large construction sites
- with the thixotropic setting, application of 40 g/cm² in one working step is not a problem

NEW
in our
range



Road Construction Materials





BORNIT® - Edge Modul

for the new basic unit BORNIT®-Flexomat 3.0



BORNIT® Edge Sealing

Economic and efficient application of **BORNIT® Edge Flex** and **BORNIT® Edge Sealant** with the **BORNIT® Flexomat 3.0** in connection with the new **BORNIT® Edge Module**

- for secure sealing and protection of the elevated edge of an asphalt body against laterally penetrating water
- also on slightly moist substrates, material application of 40 g per cm of asphalt thickness per running metre is not a problem



BORNIT® Joint Treatment of base, binder and surface layers

Economic and efficient application of **BORNIT® Joint Flex** with the **BORNIT® Flexomat 3.0** in connection with the new **BORNIT® Edge Module**

- up to a width of 40 cm, application of the binding agent on the entire surface of the joint area in one working step
- here, too, material application of 40 g per cm per running metre is not a problem, also on slightly moist substrates



Specialist dealer:

Address/Stamp:

Contact/Extension number:

We request:

- a call
- information via mail
- a visit from the field service

YouTube



QR-BORNIT-YouTube-TV-Channel

